SECTION 1: Identification

1.1 GHS Product identifier

	Product name	Nilotron Aerosol Refill - Tango Mango
	Product number	05402
1.4	Supplier's details	
	Name	Hospeco Brands Group
	Address	Cleveland OH 44143
	Telephone Fax email	800-321-9832 800-362-0073 www.hospecobrands.com
	National contact	
	Name Address	ESG Asia Pacific NZ 61 Seaview Road 5040 Lower Hutt Wellington New Zealand
	Telephone	+64 4568 4126

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

GHS classification in accordance with: (US) OSHA (29 CFR 1910.1200)

- Flammable aerosols, Cat. 1
- Gases under pressure, compressed gas
- Eye damage/irritation, Cat. 2A
- Sensitization, skin, Cat. 1
- Specific target organ toxicity (single exposure), Cat. 3

2.2 GHS label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)	
H222	Extremely flammable aerosol
H280	Contains gas under pressure; may explode if heated
H319	Causes serious eye irritation
H317	May cause an allergic skin reaction
H336	May cause drowsiness or dizziness
Precautionary statement(s)	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with
	local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Component	Concentration		
Acetone (CAS no.: 67-64-1; EC no.: 200-662-2; Index no.: 606-001-00-8)	> 50 - <= 100 % (weight)		
CLASSIFICATIONS: Flammable liquids, Cat. 2; Specific target organ toxicity (single exposu			
Cat. 2. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irr dizziness.	ritation; H336 - May cause drowsiness or		
Isobutane (CAS no.: 75-28-5; EC no.: 200-857-2; Index no.: 601-004-01-8)	> 10 - <= 25 % (weight)		
CLASSIFICATIONS: Flammable gases, Cat. 1; Fail: No text found to return.; Carcinogenicity, Cat. 1A; Germ cell mutagenicity, Cat. 1B. HAZARDS: H220 - Extremely flammable gas; H340 - May cause genetic defects [route]; H350 - May cause cancer [route].			
Propane gas (CAS no.: 74-98-6; EC no.: 200-827-9; Index no.: 601-003-00-5)	> 2.5 - <= 10 % (weight)		
CLASSIFICATIONS: Flammable gases, Cat. 1; Press. Gas. HAZARDS: H220 - Extremely flammable gas.			
N-BUTANE (CAS no.: 106-97-8; EC no.: 203-448-7; Index no.: 601-004-01-8)	<= 2.5 % (weight)		
CLASSIFICATIONS: Flammable gases, Cat. 1; Fail: No text found to return.; Carcinogenicity HAZARDS: H220 - Extremely flammable gas; H340 - May cause genetic defects [route]; H3			
Fragrance	<= 2.5 % (weight)		

CLASSIFICATIONS: Flammable liquids, Cat. 4; Acute toxicity, oral, Cat. 4; Acute toxicity, inhalation, Cat. 4; Skin corrosion/irritation, Cat. 2; Serious eye damage/eye irritation, Cat. 2; Sensitization, respiratory, Cat. 1; Hazardous to the aquatic environment, short-term (acute), Cat. 2; Hazardous to the aquatic environment, long-term (chronic), Cat. 2. HAZARDS: H227 - Combustible liquid; H302 - Harmful if swallowed; H315 - Causes skin irritation; H319 - Causes serious eye irritation; H332 - Harmful if inhaled; H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled; H401 - Toxic to aquatic life; H411 - Toxic to aquatic life with long lasting effects.

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

General advice	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
lf inhaled	Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.
In case of skin contact	Immediately wash with water and soap and rinse thoroughly.
In case of eye contact	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
If swallowed	If symptoms persist consult doctor.

- **4.2 Most important symptoms/effects, acute and delayed** No further relevant information available.
- **4.3** Indication of immediate medical attention and special treatment needed, if necessary No further relevant information available.

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials. Foam. Dry powder. Carbon dioxide. Water spray. Sand.

- 5.2 Specific hazards arising from the chemical No further relevant information available.
- 5.3 Special protective actions for fire-fighters No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and materials for containment and cleaning up Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

Protective Action Criteria for Chemicals · PAC-1: 67-64-1 acetone 200 ppm 75-28-5 isobutane 5500* ppm 74-98-6 propane 5500* ppm 106-97-8 butane, pure 5500* ppm 110-91-8 morpholine 30 ppm 142-90-5 dodecyl methacrylate 6.9 ppm 5989-27-5 (R)-p-mentha-1,8-diene 15 ppm 91-64-5 Coumarin 0.88 mg/m³ · PAC-2: 67-64-1 acetone 3200* ppm 75-28-5 isobutane 17000** ppm 74-98-6 propane 17000** ppm 106-97-8 butane, pure 17000** ppm 110-91-8 morpholine 1,300 ppm 142-90-5 dodecyl methacrylate 76 ppm 5989-27-5 (R)-p-mentha-1.8-diene 67 ppm 91-64-5 Coumarin 9.7 mg/m³ · PAC-3: 67-64-1 acetone 5700* ppm 75-28-5 isobutane 53000*** ppm 74-98-6 propane 33000*** ppm 106-97-8 butane, pure 53000*** ppm 110-91-8 morpholine 8000** ppm 142-90-5 dodecyl methacrylate 460 ppm 5989-27-5 (R)-p-mentha-1,8-diene 170 ppm 91-64-5 Coumarin 58 mg/m³

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. · Information about protection against explosions and fires: Do not spray on a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep receptacle tightly sealed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. Acetone (CAS: 67-64-1)

PEL (Inhalation): 1000 ppm (OSHA) OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 250 ppm (NIOSH) OSHA Annotated Table Z-1, www.osha.gov

TLV® (Inhalation): 250 ppm, (ST) 500 ppm; USA (ACGIH) OSHA Annotated Table Z-1, www.osha.gov

2. Isobutane (CAS: 75-28-5 EC: 200-857-2) TLV® (Inhalation): 1000 ppm

3. Propane (CAS: 74-98-6)

PEL (Inhalation): 1000 ppm (OSHA) OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 1000 ppm (NIOSH) OSHA Annotated Table Z-1, www.osha.gov

4. N-BUTANE (CAS: 106-97-8 EC: 203-448-7)

REL (Inhalation): 800 ppm

TLV® (Inhalation): 1000 ppm

8.2 Appropriate engineering controls

Provide eyewash station.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

If contact is likely, safety glasses with side shields are recommended.

Skin protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

SECTION 9: Physical and chemical properties and safety characteristics

Basic physical and chemical properties

Physical state Appearance Odor Odor threshold Melting point/freezing point Boiling point or initial boiling point and boiling range Gas Aerosol Characterisitc No data available. No data available. -44 °C (-47.2 °F) (

Flammability Lower and upper explosion limit/flammability limit Flash point Explosive properties Auto-ignition temperature Decomposition temperature Oxidizing properties pH Kinematic viscosity Solubility Partition coefficient n-octanol/water (log value) Vapor pressure Evaporation rate Density and/or relative density Relative vapor density Flammable 1.8 Vol % Lower; 13 Vol % Upper <0 °C (<32 °F) No data available. 860 °F (460 °C) No data available. No data available. No data available. Not miscible or difficult to mix. No data available. 3000 hPA (2.300 mm Hg) No data available. No data available.

Supplemental information regarding physical hazard classes Solvent Content:

Organic solvents: 83.8% VOC content: 26.11% Solid content: 3.6%

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

No decomposition if used according to specifications.

- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5** Incompatible materials No further relevant information available.

10.6 Hazardous decomposition products No dangerous decomposition products known.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

· LD/LC50 values that are relevant for classification: 67-64-1 acetone Oral LD50 5,800 mg/kg (rat)

Dermal LD50 20,000 mg/kg (rabbit)

Skin corrosion/irritation No irritant effect.

Serious eye damage/irritation

Irritating effect.

Respiratory or skin sensitization Sensitization possible through skin contact.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

IARC (International Agency for Research on Cancer)
110-91-8 morpholine 3
5989-27-5 (R)-p-mentha-1,8-diene 3
91-64-5 Coumarin 3
NTP (National Toxicology Program)
None of the ingredients is listed.
OSHA-Ca (Occupational Safety & Health Administration)
None of the ingredients is listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

STOT-single exposure

May cause drowsiness and dizziness.

SECTION 12: Ecological information

Toxicity

No further relevant information available.

Persistence and degradability

No further relevant information available.

Bioaccumulative potential

No further relevant information available.

Mobility in soil

No further relevant information available.

Results of PBT and vPvB assessment

Not applicable

Endocrine disrupting properties

No further relevant information available.

Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

Disposal methods

Product disposal

Disposal must be made according to official regulations.

Packaging disposal

Disposal must be made according to official regulations.

SECTION 14: Transport information

DOT (US)

UN Number: 1950 Class: 2.1 Packing Group: Proper Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity) Reportable quantity (RQ): Marine pollutant: Poison inhalation hazard:

IMDG

UN Number: 1950 Class: 2.1 Packing Group: EMS Number: F-D, S-U Proper Shipping Name: AEROSOLS

ΙΑΤΑ

UN Number: UN1950 Class: 2.1 Packing Group: Not applicable Proper Shipping Name: Aerosols, flammable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

Chemical name: Acetone CAS number: 67-64-1

New Jersey Right To Know Components

Common name: ACETONE CAS number: 67-64-1

New Jersey Right To Know Components Common name: ISOBUTANE

CAS number: 75-28-5

New Jersey Right To Know Components Common name: PROPANE CAS number: 74-98-6

New Jersey Right To Know Components Common name: BUTANE CAS number: 106-97-8

Pennsylvania Right To Know Components Chemical name: 2-Propanone CAS number: 67-64-1

Pennsylvania Right To Know Components Chemical name: Propane

CAS number: 74-98-6

Pennsylvania Right To Know Components Chemical name: Propane, 2-methyl-

CAS number: 75-28-5

Pennsylvania Right To Know Components Chemical name: Butane

CAS number: 106-97-8

HMIS Rating

Nilotron Aerosol Refill - Tango Mango		
HEALTH	2	
FLAMMABILITY	4	
PHYSICAL HAZARD	1	
PERSONAL PROTECTION		

NFPA Rating



SECTION 16: Other information